





Mod. **6125** - 110 V  
 Mod. **6122** - 230 V  
 Mod. **6128** - 400 V

Elettropompa ad ingranaggi per travasi di oli, antigelo, gasolio, acqua, a media pressione; garantisce una regolarità di flusso e una contenuta rumorosità. Corpo pompa in acciaio inox, ingranaggi in nilon ed albero in acciaio inox.

*Electric gear pump for dispensing fluids as oil, antifreeze, diesel, water, at medium pressure; smooth output of the product and reduced noise. Pump body in stainless steel, gears in nylon and shaft in stainless steel.*



Mod.	Alimentazione Feeding	Potenza Power	P. uscita Output Pressure	Portata Flow rate (lt/min)	Attacchi Connections	Peso Weight	Dimensioni Sizes (X-Z-Y) (mm)
6125	110 V - 60 Hz	0.55 kw	15 bar	10.5	F 1/2"BSP	7.5 kg	150x300x190
6122	230 V - 50 Hz	0.55 kw	15 bar	10.5	F 1/2"BSP	7.5 kg	150x300x190
6128	400 V - 50 Hz	0.55 kw	15 bar	10.5	F 1/2"BSP	7.5 kg	150x300x190




Mod. **6141**


Elettropompa ad ingranaggi per travasi di oli, antigelo, gasolio, acqua, a media pressione; garantisce una regolarità di flusso e una contenuta rumorosità. Corpo pompa in acciaio inox, ingranaggi in nilon ed albero in acciaio inox.

Fornita completa di pressostato e accumulatore.

*Electric gear pump for dispensing fluids as oil, antifreeze, diesel, water, at medium pressure; smooth output of the product and reduced noise. Pump body in stainless steel, gears in nylon and shaft in stainless steel. The kit includes cut-off switch, valve and pressure accumulator.*



Mod.	Aliment. Feeding	Potenza Power	P. uscita Output Pressure	Portata Flow rate (lt/min)	Attacchi Connections	Peso Weight	Dimensioni Sizes (X-Z-Y) (mm)
6141	230 V - 50 Hz	0.55 kw	12 bar	10.5	F 1/2"BSP	11.5 kg	150x340x190



Mod. **6437**

Elettropompa ad eccentrico per travasi di olio, olio esausto, antigelo, gasolio, a bassa pressione. Corpo pompa in alluminio, tenute in NBR ed albero in ottone.

*Electric pump for dispensing fluids as oil, waste oil, antifreeze, diesel, at low pressure. Pump body in aluminium, gaskets in NBR and shaft in brass.*



Mod.	Alimentaz. Feeding	Potenza Power	P. uscita Output pressure	Portata Flow rate (lt/min)	Attacchi Connections	Peso Weight	Dimensioni Sizes (X-Z-Y) (mm)
6437	230 V - 50 Hz	0.52 kw	1.5 bar	15	F 3/4"BSP	8.5 kg	150x340x210

