

**SPRING DRIVEN HOSE REEL GUIDE ARM VARIABLE POSITION Ø MAX 1'' UP TO 15 mt.**



Mod. 9029-9084

Powder coated steel spring driven hose reel , open type , guide arm variable position . Suitable up t o max. 20 Ø 3/4' ( 15 mt.Ø 1'').

**Mod. 9029 – 9084** Basic hose-reel is furnished without hose , and it can be used for diesel , low pressure water and air hoses rewinding To select the hose consult the footnote



**Mod. 9768**  
swing  
bracket for  
9029

**Mod. 9777**  
swing  
bracket for  
9084



Mod. 9767  
Mod. 9768  
Mod. 9758

Stainless steel spring driven hose reel , open type , guide arm variable position . Suitable up t o max. 20 Ø 3/4' ( 15 mt.Ø 1'').

**Mod. 9527 – 9534** Basic hose-reel is furnished without hose , and it can be used for diesel , low pressure water and air hoses rewinding

To select the hose consult the footnote



Mod. 9527-9534



**Mod. 9765**  
swing  
bracket for  
9527

**Mod. 9770**  
swing  
bracket for  
9534



Mod. 9760  
Mod. 9765  
Mod. 9775

Mod.	Max. Pressure	Connections In - Out	I.D. swivel mm	Max Ø hose	Hose assembly capacity Max. 3/4' 1''	Weight k.	Spool width mm	Mod. Swing bracket on request	Dimensions (X-Z-Y)
9029	20 bar	M 1' F 1'	20	1'	10 mt-8 mt	18	150	9768	270x530x490
9084	20 bar	M 1' F 1'	20	1'	20 mt-15mt	27	150	9777	270x590x600
9527	20 bar	M 1' F 1'	20	1'	10 mt-8 mt	18	150	9765	270x590x600
9534	20 bar	M 1' F 1'	20	1'	20 mt-15mt	27	150	9770	270x590x600

Advised hoses for these models according to types of fluid and length

Type of fluid	Ø hose	8 mt	10 mt	15 mt.	20 mt.
Low pressure water	¾ - 30 bar	18908	18910	18915	18920
Air / water	¾ - 30 bar	39908	39910	39915	39920
Diesel	¾ 17 bar	28808	28810	28815	28820
	1' 17 bar	289608	289610	289615	-