

SPRING DRIVEN HOSE REELS

guide arm variable position series EVO MY10 Ø 1/2" up to 25 m.



Powder coated steel spring driven hose reel , open type , guide arm variable position series EVO MY10 .Suitable up t o max. 25 mt. 1/2 " bsp .

Mod. 9090 – 9091 – 9092 - 9093

This series is the development of the former adjustable guide arms series and features an unique bracket , enabling a stronger structural support.

This series mounts a new spring with more spirals . The fluid passage is granted by a new zinc plated flanged hose-connection which on request may be in stainless steel AISI 316



Mod. 9767 swing bracket for 9090-9091

Mod. 9768 swing bracket for 9092

Mod. 9758 swing bracket for 9093



AISI 304 Stainless steel spring driven hose reel , open type , guide arm variable position series **EVO MY10** .Suitable up t o max. 25 mt. 1/2 " bsp .

Mod. 9590 – 9591 – 9592 - 9593

This series is the development of the former adjustable guide arms series and features an unique bracket , enabling a stronger structural support.

This series mounts a new spring with more spirals . The fluid passage is granted by a new interchangeable flanged hose-connection .



Mod. 9760 swing bracket for 9590-9591

Mod. 9765 swing bracket for 9592

Mod. 9775 swing bracket for 9593

Mod.	Max. Pressure	Connections In - Out	I.D. swivel mm	Max Ø hose	Hose assembly capacity Max. 3/8 1/2	Weight k.	Spool width mm	Mod. Swing bracket on request	Dimensions (X-Z-Y)
9090	600 bar	M 1/2' F 1/2 '	12	1/2 '	15 mt	12	120	9767	240x550x450
9091	600 bar	M 1/2' F 1/2 '	12.	1/2 '	20 – 15 mt	13	120	9767	240x550x450
9092	600 bar	M 1/2' F 1/2 '	12	1/2 '	25 – 20 mt	16	150	9768	270x550x450
9093	600 bar	M 1/2' F 1/2 '	12	1/2 '	25 mt	19	200	9758	310x550x450
9590	200 bar	M 1/2' F 1/2 '	10	1/2 '	15 mt	12	120	9760	240x550x450
9591	200 bar	M 1/2' F 1/2 '	10	1/2 '	20 – 15 mt	13	120	9760	240x550x450
9592	200 bar	M 1/2' F 1/2 '	10	1/2 '	25 – 20 mt	16	150	9765	270x550x450
9593	200 bar	M 1/2' F 1/2 '	10	1/2 '	25 mt	19	200	9775	310x550x450

Advised hoses for these models according to the types of fluid and lengths

Type of fluid	Ø hose	10 mt	15 mt	20 mt.	25 mt.
Oil / antifreeze	1/2' R1T 160 bar	28710	28715	28720	28725
Grease	1/4' R2T 400 bar	4510	4515	4520	4525
High pressure water	3/8' R2T 330 bar	4710	4715	4720	4725
Air / water	3/8 ' 40 bar	3810	3815	3820	3825